SCHEDULE B - STANDARDS

DISTRICT CODES

STANDARDS R-1A R-1 R-2 R-3 R-4 1. Min. lot area (in s.f.) 120,000 40,000 20,000 12,000 7,500 1a. Contiguous buildable area 40,000 40000/30,000 20,000 12,000 75,000 2. Min. lot area per d.u. (in s.f.) 120,000 10,000 7,500 7,500 2a. Min. lot area per one-bedroom d.u. (in s.f.) N/A N/A N/A N/A	R-5 5,000 5,000 5,000 N/A 50' 50'
1a. Contiguous buildable area 40,000 40000/30,000 20,000 12,000 75,000 2. Min. lot area per d.u. (in s.f.) 120,000 10,000 7,500 7,500 2a. Min. lot area per one-bedroom d.u. (in s.f.) N/A N/A N/A N/A	5,000 5,000 N/A 50'
2. Min. lot area per d.u. (in s.f.) 120,000 10,000 7,500 7,500 2a. Min. lot area per one-bedroom d.u. (in s.f.) N/A N/A N/A N/A N/A	5,000 N/A 50'
2a. Min. lot area per one-bedroom d.u. (in s.f.) N/A N/A N/A N/A N/A	N/A 50'
(in s.f.) N/A N/A N/A N/A	50'
	50'
3. Min. dimensions of square on lot 300' 150' 125' 75' 60'	50'
4. Min. lot frontage 270' 135' 115' 75' 60'	
5. Maximum number of stories for a	
building 3 3 3 3 3	3
6. Max. height of a building or story 40' 40' 40' 40' 40'	40'
7. Min. setback from street line 50' 40' 40' 30' 25'	25'
8. Min. setback from rear line 50' 30' 30' 25'	25'
9. Min. setback from side or other	
property 50' 30' 20' 15' 8'	8'
10. Min. setback from Residence District	
boundary line none none none none	none
11. Max. lot coverage as % of lot area 5% 15% 20% 25%	30%
11a. Max. lot coverage of accessory	
structure as a percent of lot area 1% 2.50% 3% 5% 5%	5%
12. Max. total impervious lot coverage as a	
% of lot area 30% 30% 35% 40% 50%	50%
13. Max. floor area as a % of lot area 10% 20% 30% 40% 50%	50%
14. Min. floor area on ground floor for one-	
story dwelling (in s.f.) 1,100 1,100 900 900	900
15. Min. total floor area on all floors for	
split-level dwelling (in s.f.) 1,100 1,100 1,100 1,100 1,100	1,100
16. Min. floor area for two or more story	
dwelling (in s.f.)	
<u>Ground Floor</u> <u>900</u> <u>900</u> <u>800</u> <u>800</u>	<u>800</u>
Total Floor Area 1,350 1,350 1,350 1,100 1,100	1,100
17. Min. floor area for each d.u. (in s.f.) 550 550 550 550	550

N/A means Not Applicable

SCHEDULE B - STANDARDS

DISTRICT CODES

	STANDARDS	CA-1	CA-2	CA-3	CB-1	CB-2	RBD	RFD
1.	Min. lot area (in s.f.)	80,000	15,000	6,000	40,000	15,000	40,000	20,000
1a.	Contiguous buildable area							
2.	Min. lot area per d.u. (in s.f.)	80,000	15,000	3,600	40,000	15,000	40,000	500
2a.	Min. lot area per one-bedroom							
	d.u. (in s.f.)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
3.	Min. dimensions of square on lot	200'	80'	50'	150'	80'	200'	100'
4.	Min. lot frontage	175'	80'	50'	135'	80'	170'	100'
5.	Maximum number of stories							
	for a building	3	3	none	3	3	3	none
6.	Max. height of a building or story	40'	40'	40'	40'	40'	40'	60'*
7.	Min. setback from street line	50'	40'	none	50'	40'	50'	10'
8.	Min. setback from rear line	50'	40'	12'	20'	20'	25'	25'
9.	Min. setback from side or							
	other property	20'	12'	none	20'	12'	25'	10'
10.	Min. setback from Residence							
	District boundary line	50'	40'	20'	50'	40'	50'	N/A
11.	Max. lot coverage as % of lot area	25%	25%	75%	25%	35%	40%	75%
11a	. Max. lot coverage of accessory							
	structure as a percent of lot area							
12.	Max. total impervious lot coverage as							
	a % of lot area	75%	85%	90%	80%	85%	75%	90%
13.	Max. floor area as a % of lot area	50%	50%	150%	50%	50%	80%	350**
14.	Min. floor area on ground floor for							
	one- story dwelling (in s.f.)	900	900	900	900	900	900	N/A
15.	Min. total floor area on all floors							
	for split-level dwelling (in s.f.)	1,000	1,000	1,000	1,000	1,000	1,000	N/A
16.	Min. floor area for two or more							
	story dwelling (in s.f.)							
	<u>Ground</u>	<u>800</u>	<u>800</u>	<u>800</u>	<u>800</u>	<u>800</u>	<u>800</u>	
	<u>Floor</u> Total	1,100	1,100	1,100	1,100	1,100	1,100	N/A
17.	Min. floor area for each d.u. (in s.f.)	550	550	550	550	550	600	650'

N/A means Not Applicable

^{*}Refer to Paragraph 24.3 concerning excess height

^{**}Within any building, floor area devoted to parking shall not be included in the calculation of maximum floor area ratio.

^{***}Within an existing structure to be rehabilitated, the Commission may permit not more than 10% of the dwelling units within said structure to be reduced to lot less than 550 square feet.

SCHEDULE B - STANDARDS

DISTRICT CODES

STANDARDS	IA-1	IA-2	IA-3	IB-1	IB-2	LIP	OPD
1. Min. lot area (in s.f.)	120,000	80,000	40,000	80,000	20,000	80,000	120,000
1a. Contiguous buildable area	N/A						
2. Min. lot area per d.u. (in s.f.)	N/A	80,000	40,000	80,000	20,000	80,000	120,000
2a. Min. lot area per one-bedroom d.u.							
(in s.f.)	N/A						
3. Min. dimensions of square on lot	250'	200'	150'	200'	100'	200'	200'
4. Min. lot frontage	50'	175'	135'	175'	90'	175'	50'
5. Maximum number of stories for a							
building	none	none	none	none	none	3	none
6. Max. height of a building or story	60'	60'	60'	60'	60'	40'	60'*
7. Min. setback from street line	50'	50'	25'	50'	25'	75'	75'
8. Min. setback from rear line	50'	25'	25'	25'	12'	25'	40'
9. Min. setback from side or other							
property	50'	25'	25'	25'	12'	25'	40'
10. Min. setback from Residence District							
boundary line	75'	50'	50'	50'	25'	75'	75'
11. Max. lot coverage as % of lot area	30%	40%	40%	40%	75%	30%	20%
11a. Max. lot coverage of accessory							
structure as a percent of lot area							
12. Max. total impervious lot coverage as a							
% of lot area	75%	75%	75%	75%	80%	75%	65%
13. Max. floor area as a % of lot area	90%	80%	80%	80%	150%	50%	60%
14. Min. floor area on ground floor for one-							
story dwelling (in s.f.)	N/A	900	900	900	900	900	900
15. Min. total floor area on all floors for							
split-level dwelling (in s.f.)	N/A	1,000	1,000	1,000	1,000	1,000	1,000
16. Min. floor area for two or more story							
dwelling (in s.f.)							
<u>Ground Floor</u>	<u>N/A</u>	<u>800</u>	<u>900</u>	<u>800</u>	<u>800</u>	<u>800</u>	<u>800</u>
Total Floor Area		1,100	1,350	1,100	1,100	1,100	1,100
17. Min. floor area for each d.u. (in s.f.)	N/A	550	550	550	550	550	550

N/A means Not Applicable

^{*}Refer to Paragraph 24.3 concerning excess height